





PIG® Drive-Over Build-A-Berm® Barrier T Connector

PLR135 For 2" High Drive-Over Build-A-Berm Barrier,2 per box

Build a semi-permanent barrier layout and then drive over it! Use these drive-over T Connectors, along with our PIG Spill Berms and Corners, and contain spills around your unique machinery setup or storage area. Includes the option for dual containment areas separated by a shared center line.

- The Drive-Over Barrier provides semipermanent containment in high-traffic areas on concrete, asphalt or most sealed surfaces
- Create any configuration by combining with other Build-A-Berm components; ends overlap and can be sealed together for liquid-proof containment
- Can be used to help create two separate containment areas with a shared center line in order to take up less floor space
- Durable enough to withstand indoor or outdoor traffic from trucks, loaded tow motors and other heavy vehicles
- Constructed of 40 oz, vinyl-coated fabric with an open-cell foam core; berm compresses to approximately 0.25" when driven over; springs back to shape when vehicles pass
- When used with standard high-visibility yellow Build-A-Berm Barriers, orange color indicates area where drivers can enter and exit
- Secure to floor with sealant (sold separately) and reinforce with predrilled aluminum mounting strips (included) and steel anchors (included); seal seams with vinyl cement (sold separately)

Style	T Connector
Use With	2" High Drive-Over Build-A-Berm Barrier
Dimensions	11.5" W x 17.5" L x 1.5" H
Barrier Height	2" H
Brand	PIG
Temperature Limit	Works from -22°F to 160°F
Color	Orange
Traffic	Vehicle Traffic

Specifications

Sold as	2 per box
Weight	1.4 lbs.
New Pig Patent	5,820,297
Composition	Cover: 40 oz. PVC Core: Open-Cell Polyurethane Foam Strips: Aluminum Anchors: Galvanized Steel
UNSPSC	24101907
Metric Equivalent	
Weight	.6 kg
Dimensions	29cm W x 44cm L x 3.8cm H
Technical Information	
USOnly	
This product can ONLY be shipped to the United States.	
Technical Documents	
PIG Build-A-Berm® Barrier	
Instructions for Lloing DIC® Build & Borm® Porrior	

Instructions for Using PIG® Build-A-Berm® Barrier

40 CFR 112.7

40 CFR 122.26

40 CFR 264.175



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com