













**UNSPSC** 

## **Specifications**

Max Liquid Temp Exposure	Max Exposure Limit 225°F for up to 30 Minutes
Dimensions	2" W x 4' L x 1.5" H
Application	Doorways
Barrier Dimensions	One 2" W x 4' L x 1.5" H Section
Barrier Height	1.5" H
Brand	PIG
Color	Yellow
Ideal For	Doorway Spill Response
Install/Deploy Type	Temporary/Removable Barrier
Temperature Limit	Works from 0°F to 160°F
Traffic	Non-Weight Bearing
Sold as	1 per box
Weight	4 lbs.
New Pig Patent	5,236,281
Composition	Polyurethane

24101907

### PIG® DoorBlocker Dike

PLR213 Ideal For Doorway Spill Response,One 2" W x 4' L x 1.5" H Section

Specially designed spill dike seals off doorways to protect against spreading spills, rising water or washdown liquids.

- Unique 45-degree wedge design fits snugly against doorjambs to stop the spread of liquids
- Ideal as a barrier in doorways during washdown operations, as a dam to control or contain spilled liquids or as a diverter to direct rising water or liquid away from equipment or supplies
- Reusable dike cleans easily with soap and water
- Polyurethane material resists water, oils and many chemicals
- High-visibility yellow top color draws attention to spill for increased safety
- Fits any doorway up to 4' wide
- Light-weight dike is easy to handle and deploy

Pigalog® Page Number Page 158

# Metric Equivalent

Weight 1.8 kg

Dimensions 5.1cm W x 122cm L x 3.8cm H

### **Technical Information**

#### **Technical Documents**

PIG SpillBlocker Dikes, DrainBlocker Drain Covers and other Blockers

PIG Spillblocker Dike Instructions

Technical Data Sheet for PIG® Blocker Family

Urethane Use, Care and Storage

40 CFR 112.7

40 CFR 122.26



# One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com