




PIG® SpillBlocker® Rough Surface Dike

PLR230 Ideal For One-Time-Use Emergency Spill Response, One 2" W x 10' L x 2.25" H Section

Our Rough-Surface Dike stops spills on asphalt in their tracks with a liquid-tight tacky bottom layer that seeps into surface cracks.

- Tear-resistant top layer and a super-tacky bottom layer create a tight, liquid-proof seal on rough surfaces
- Bottom layer fills into surface cracks to form a liquid-tight seal
- Fast protection for when a spill is heading right for your drain on a rough surface; just set dike down with sticky side away from surface, turn dike over and press into place
- Intended for one-time, limited term use; ideal for containing hazardous or other liquids on rough surfaces
- Confines and diverts fluids without absorbing them, making cleanup simple
- 2.25" height contains spills up to 2" deep
- Connector piece included to create a liquid-proof seal and allow you to join as many sections as needed
- Polyurethane material resists water, oils and many chemicals
- High-visibility yellow top color draws attention to spill for increased safety



Specifications

Max Liquid Temp Exposure	Max Exposure Limit 225°F for up to 30 Minutes
Dimensions	2" W x 10' L x 2.25" H
Application	Rough Surfaces and Asphalt
Barrier Dimensions	One 2" W x 10' L x 2.25" H Section
Barrier Height	2.25" H
Brand	PIG
Color	Yellow
Ideal For	One-Time-Use Emergency Spill Response
Install/Deploy Type	Temporary/Removable Barrier
Storage Temp Range	Store Between 0°F and 120°F

Temperature Limit	Works from 0°F to 160°F
Traffic	Non-Weight Bearing
Sold as	1 per box
Weight	13 lbs.
New Pig Patent	5,236,281
# per Pallet	32
Composition	Polyurethane
Includes	1 - PIG® SpillBlocker® Rough Surface Dike 1 - Connector 1 - Polyethylene Disposal Bags (BAG201-S)
UNSPSC	24101907
Pigalog® Page Number	Page 159

Metric Equivalent

Weight	5.9 kg
Dimensions	5.1cm W x 3m L x 5.7cm H

Technical Information

Technical Documents

[PIG SpillBlocker Dikes, DrainBlocker Drain Covers and other Blockers](#)

[Instructions for PIG SpillBlocker Rough Surface Dike](#)

[Technical Data Sheet for PIG® Blocker Family](#)

[Urethane Use, Care and Storage](#)

[40 CFR 112.7](#)

[40 CFR 122.26](#)



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com