









PLR283 Ideal For Long-Term Custom Containment, High-Traffic Areas,5.5" W x 12' L x 2" H,1 each

Drive-over barrier springs back into shape when heavy vehicles pass. Custom containment berm helps you control liquids in high-traffic areas.

- The Drive-Over Barrier provides semipermanent containment in high-traffic areas on concrete, asphalt or most sealed surfaces
- Constructed of 40-ounce, vinyl-coated fabric with an open-cell foam core; berm compresses to approximately 1/4" when driven over; springs back to shape when vehicles pass
- Durable enough to withstand indoor or outdoor traffic from trucks, loaded tow motors and other heavy vehicles with sufficient ground clearance
- Secure to floor with sealant (not included) and reinforce with predrilled aluminum mounting strips (included) and steel anchors (included); seal seams with vinyl cement (not included)
- Combine with Build-A-Berm Barrier Vented Corners to create liquid-proof containment; ends overlap and seams can be sealed together with Industrial-Strength Vinyl Cement (sold separately)
- When used with standard high-visibility yellow Build-A-Berm Barriers, orange color indicates area where drivers can enter and exit
- Sealant, industrial-strength vinyl cement and barrier vented corner pieces sold separately



### **Specifications**

Style	Straight Section
Dimensions	5.5" W x 12' L x 2" H
Barrier Height	2" H
Brand	PIG
Ideal For	Long-Term Custom Containment, High-Traffic Areas
Install/Deploy Type	Glued In Place Barrier
Color	Orange
Temperature Limit	Works from -22°F to 160°F

Traffic	Vehicle Traffic
Sold as	1 each
Weight	11.5 lbs.
New Pig Patent	5,820,297
# per Pallet	32
Composition	Cover: 40 oz. Vinyl-Coated Fabric Core: Open-Cell Polyurethane Foam Strips: Aluminum Anchors: Galvanized Steel
Includes	1 - 12' Straight Section Barrier 6 - 4' L x 1/8" H x 1" W Mounting Strips 33 - 1/4" x 1 5/8" Anchors
UNSPSC	24101907
Pigalog® Page Number	Page 155

## Metric Equivalent

Weight 5.2 kg

**Dimensions** 14cm W x 3.7m L x 5.1cm H

#### **Technical Information**

#### **Technical Documents**

PIG Build-A-Berm® Barrier

Instructions for PIG Drive-Over Build-A-Berm Barrier

40 CFR 112.7

40 CFR 122.26



# One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com