











PIG® Drive-Over Build-A-Berm® Barrier Vented 90° Corner

PLR515 For 1.5" High Drive-Over Build-A-Berm Barrier,2 per box

Drive-over barrier springs back into shape when heavy vehicles, carts, dollies and pallet jacks pass. Custom containment berm helps you control liquids in high-traffic areas.

- The Drive-Over Barrier provides semipermanent containment in high-traffic areas on concrete, asphalt or most sealed surfaces
- Constructed of 40-ounce, vinyl-coated fabric with an open-cell foam core; berm compresses to approximately 1/4" when driven over; springs back to shape when vehicles pass
- 1.5" height accommodates low-clearance traffic like pallet jacks, heavy carts and dollies; durable enough to withstand indoor or outdoor traffic from trucks, loaded tow motors and other heavy vehicles
- Secure to floor with sealant (sold separately) and reinforce with predrilled aluminum mounting strips (included) and steel anchors (included); seal seams with vinyl cement (sold separately)
- Create any configuration by combining with other Build-A-Berm components; ends overlap and can be sealed together for liquid-proof containment
- When used with standard high-visibility yellow Build-A-Berm Barriers, orange color indicates area where drivers can enter and exit
- Vent allows built-up air pressure caused by heavy vehicles driving over connected heavyduty sections to escape without rupturing the seams of your barrier
- Join two 1.5"-high Drive-Over Build-A-Berm straight sections at a 90-degree angle (sold separately)



Specifications

Style	90° Corner
Use With	1.5" High Drive-Over Build-A-Berm Barrier
Dimensions	4.5" W x 6.75" L x 1.5" H

Barrier Height	1.5" H
Brand	PIG
Temperature Limit	Works from -22°F to 160°F
Color	Orange
Traffic	Vehicle Traffic
Sold as	2 per box
Weight	2.25 lbs.
New Pig Patent	5,820,297
Composition	Cover: 40 oz. PVC Core: Open-Cell Polyurethane Foam Strips: Aluminum Anchors: Galvanized Steel
UNSPSC	24101907
Pigalog® Page Number	Page 155

Metric Equivalent

Weight 1 kg

Dimensions 11cm W x 17cm L x 3.8cm H

Technical Information

Technical Documents

PIG Build-A-Berm® Barrier

Instructions for PIG Drive-Over Build-A-Berm Barrier

40 CFR 112.7

40 CFR 122.26



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com