

PIG® Build-A-Berm® Self-Rising Drive-Over Barrier

PLR518 Ideal For Long-Term Custom Containment, High-Traffic Areas, 7" x 9' x 4", 1 each

Drive right into and out of your 4" tall Build-A-Berm containment area; when a spill strikes, this special barrier rises to the occasion.

- Berm wall lays flat to allow forklifts, pallet jacks and drum trucks to drive-over for easy access to containment area
- In the event of a spill, drive-over gate will automatically rise with the spill level to keep liquids contained
- Berm ends can be directly connected to an existing 4"H Build-A-Berm system (sold separately)
- Ends of 4"H berm are pliable, open-cell foam core covered with vinyl; gate section is constructed of durable PVC
- Secure to floor with sealant and reinforce with predrilled aluminum mounting strips (included) and steel anchors (included); seal seams with vinyl cement (not included)



Specifications

Style	Self-Rising
Dimensions	7" W x 9' L x 4" H
Barrier Height	4" H
Brand	PIG
Ideal For	Long-Term Custom Containment, High-Traffic Areas
Install/Deploy Type	Glued In Place Barrier
Color	Orange/Yellow
Temperature Limit	Works from -22°F to 160°F
Traffic	Vehicle Traffic
Sold as	1 each
Weight	9.4 lbs.
New Pig Patent	9,498,806
# per Pallet	40

Composition

Self-Rising Barrier: PVC
 Cover: 18 oz. Vinyl-Coated Fabric
 Core: Open-Cell Polyurethane Foam
 Strips: Aluminum
 Anchors: Galvanized Steel

Includes

1 - 9' Self-Rising Barrier
8 - 1" x 24" Aluminum Strips
4 - 1" x 3.5" Aluminum Strips
33 - 1/4" x 1 5/8" Anchors

UNSPSC

24101907

Pigalog® Page NumberPage 152**Metric Equivalent****Weight**

4.3 kg

Dimensions

18cm W x 274cm L x 10cm H

Technical Information**Technical Documents**[PIG Build-A-Berm® Barrier](#)[PIG Self-Rising Drive-Over Build-A-Berm Barrier Instructions](#)[40 CFR 112.7](#)[40 CFR 122.26](#)[40 CFR 264.175](#)**New Pig**

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-03041-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com