

## PIG® Rapid Response DrainBlocker® Drain Cover

PLR601 Ideal For One-Time-Use Emergency Spill Response, For Square & Round Drains Up to 15"

Be ready for emergency response with a DrainBlocker that helps meet regs and is affordable enough to place near storm drains in all your spill-prone areas.

- Affordable design helps you meet spill plan requirements without buying more cover than you need
- Super-sealing bottom layer conforms to uneven surfaces and tightly seals drains
- Withstands exposure to diesel fuel and gasoline
- Specially designed to work in emergency spill applications; mount on a wall (bracket sold separately) or store in a spill kit
- Cover resists chemicals, oils and detergents
- Packaged in an easy-open, hi-viz storage tube so workers can find it fast and get to the spill
- For outdoor storage use a Weather-Resistant Storage Tube for PIG Rapid Response DrainBlocker Drain Cover (PLR700)



### Specifications

Traffic	Non-Weight Bearing
Use With	Square & Round Drains Up to 15"
Color	Hi-Viz Green
Dimensions	21" W x 21" L x 0.125" H
Brand	PIG
Drain Shape	Square; Round
Drain Size	Up to 15"; Up to 15" Dia.
Ideal For	One-Time-Use Emergency Spill Response
Max liquid temp exposure	Max Exposure Limit 225°F for up to 30 Minutes
Storage Temp Range	Store from 0°F to 120°F
Temperature Limit	Works from 0° to 160°F
Sold as	1 each
Weight	4.1 lbs.
New Pig Patent	8,117,686

# per Pallet	130
Composition	Top - Polypropylene Bottom - Polyurethane
UNSPSC	40141739
UV Resistant	No
Pigalog® Page Number	<u>Page 173</u>

## Metric Equivalent

Dimensions	53.3cm W x 53.3cm L x 3.2mm H
Weight	1.9 kg

## Technical Information

### Technical Documents

[PIG SpillBlocker Dikes, DrainBlocker Drain Covers and other Blockers](#)

[Urethane Use, Care and Storage](#)

[PIG® Blocker Family](#)

[40 CFR 112.7](#)

[40 CFR 122.26](#)

### Disclaimers

#### Urethane Notice

Due to the nature of softer urethane, the physical properties of these products may change over time with exposure to certain environmental conditions like temperature, humidity, and UV radiation. Typical life expectancy is 5 years. Please inspect the stored product regularly to ensure it is in a usable state. For more details and for chemical compatibility, please call Technical Services.



**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)