

# FASTLANE® Drop Over Cable Protector

PLS1550 Drop-Over Model,(2) 1.75" W x 1" H Channels,10.75" x 36" x 1.5"

Drop this economical protector over cables and cords for quick protection that helps prevent tripping.

- Open-bottom design protects ground- or floor-mounted lines; interlockable connectors let you join multiple units
- Strong polyurethane construction resists pedestrian and light vehicle traffic
- Beveled edges allow easy transition to decrease trip hazard
- Textured tread plate adds slip resistance for foot traffic
- Compact design allows easy setup, breakdown and storage
- Easy to customize by joining multiple units with interlocking connectors or by alternating colors in a high-visibility pattern
- Extra-wide, double-channel design accommodates cables and cords up to 1-3/4" wide



**CHECKERS**

| Item#      | Description | Dimensions                | Weight  |
|------------|-------------|---------------------------|---------|
| PLS1550-BK |             | 10.75" W x 36" L x 1.5" H | 10 lbs. |
| PLS1550-OR |             | 10.75" W x 36" L x 1.5" H | 10 lbs. |

## Metric Equivalent:

| Item#      | Description | Dimensions                    | Weight |
|------------|-------------|-------------------------------|--------|
| PLS1550-BK |             | 27.3cm W x 91.4cm L x 3.8cm H | 4.5 kg |
| PLS1550-OR |             | 27.3cm W x 91.4cm L x 3.8cm H | 4.5 kg |

## Specifications

|                   |                           |
|-------------------|---------------------------|
| Style             | Drop-Over Model           |
| Dimensions        | 10.75" W x 36" L x 1.5" H |
| Load Capacity UDL | 2100 lbs.                 |
| Brand             | Checkers                  |

|                             |                               |
|-----------------------------|-------------------------------|
| <b>Channels</b>             | (2) 1.75" W x 1" H            |
| <b>Temperature Limit</b>    | -40°F (-40°C) to 120°F (49°C) |
| <b>Sold as</b>              | 1 each                        |
| <b>Weight</b>               | 10 lbs.                       |
| <b>Composition</b>          | UV-Stabilized Polyurethane    |
| <b>UNSPSC</b>               | 24141510                      |
| <b>Pigalog® Page Number</b> | <a href="#">Page 231</a>      |

## Metric Equivalent

|                          |                               |
|--------------------------|-------------------------------|
| <b>Dimensions</b>        | 27.3cm W x 91.4cm L x 3.8cm H |
| <b>Load Capacity UDL</b> | 952.6 kg                      |
| <b>Weight</b>            | 4.5 kg                        |

## Technical Information



**New Pig**

World's best stuff for leaks, drips and spills.

**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)