

PIG® Pipe Wrap Repair Kit for Lines & Joints Not Under Pressure

PTY120 Non-Pressurized, For 2.5" - 4" dia.

Fast, easy way to permanently fix broken, corroded or leaking pipes to beyond their original strength.

- Each kit contains materials for restoring one unpressurized pipe or joint
- Works on most pipes, including PVC, copper, galvanized steel, rubber, lead and iron
- Materials adhere to wet or dry surfaces to allow repairs without draining pipes
- Butyl patch or PIG® Repair Putty applies underneath outer wrap to strengthen seal
- Polyurethane-impregnated fiberglass wrap exceeds original bursting pressure rating of pipes
- Nitrile gloves protect hands during repair
- Cures in approximately 30 minutes at 75°F
- Final repair is not affected by salt water
- NSF Certified for safe use on potable water lines



Specifications

Style	Pipe Patch Kit
Brand	PIG
Cure Time	30 Minutes at 75°F (24°C)
Pipe Pressure	Non-Pressurized
Pipe Size	2.5" - 4" dia.
Temperature Limit	300°F (149°C) Continuous/500°F (260°C) Intermittent
Sold as	3 per box
Weight	3.21 lbs.
Composition	Putty: Epoxy Patch: Butyl Gloves: Nitrile Wrap: Polyurethane, Fiberglass
Includes	3 - 1.5" L PIG® Multi-Purpose Epoxy Putty (2 year shelf life) (PTY230) 1 - 4"L x 4"W Butyl Patch 1 - Pair Nitrile Gloves 1 - 15'L x 4"W Polyurethane-impregnated Fiberglass Wrap
Shelf Life	2 years

Metric Equivalent

Weight	1.5 kg
--------	--------

Technical Information

CountryNoShip

This product is subject to export restrictions and cannot be shipped to: Canada, European Union, Great Britain, Japan.

Certifications, Approvals and Ratings

NSF Certified

Technical Documents

[Instructions for Using PIG® Pipe Wrap Repair Kit on Pipes Not Under Pressure](#)

[PIG® Multi-Purpose Repair Putty](#)

[PIG® Wrap for Pipes](#)

**New Pig**

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com