















**Shelf Life** 



## PIG® Pipe Wrap Repair Kit for Lines & Joints Not Under Pressure

PTY120 Non-Pressurized, For 2.5" - 4" dia.

Fast, easy way to permanently fix broken, corroded or leaking pipes to beyond their original strength.

- Each kit contains materials for restoring one unpressurized pipe or joint
- Works on most pipes, including PVC, copper, galvanized steel, rubber, lead and iron
- Materials adhere to wet or dry surfaces to allow repairs without draining pipes
- Butyl patch or PIG® Repair Putty applies underneath outer wrap to strengthen seal
- Polyurethane-impregnated fiberglass wrap exceeds original bursting pressure rating of pipes
- Nitrile gloves protect hands during repair
- Cures in approximately 30 minutes at 75°F
- Final repair is not affected by salt water
- NSF Certified for safe use on potable water lines

# Specifications

Specifications	
Style	Pipe Patch Kit
Brand	PIG
Cure Time	30 Minutes at 75°F (24°C)
Pipe Pressure	Non-Pressurized
Pipe Size	2.5" - 4" dia.
Temperature Limit	300°F (149°C) Continuous/500°F (260°C) Intermittent
Sold as	3 per box
Weight	3.21 lbs.
Composition	Putty: Epoxy Patch: Butyl Gloves: Nitrile Wrap: Polyurethane, Fiberglass
Includes	<ul> <li>3 - 1.5" L PIG® Multi-Purpose Epoxy Putty (2 year shelf life) (PTY230)</li> <li>1 - 4"L x 4"W Butyl Patch</li> <li>1 - Pair Nitrile Gloves</li> <li>1 - 15'L x 4"W Polyurethane-impregnated Fiberglass Wrap</li> </ul>

2 years

UNSPSC	31201519	
Pigalog® Page Number	Page 249	

# Metric Equivalent

Weight	1.5 kg

### **Technical Information**

### CountryNoShip

This product is subject to export restrictions and cannot be shipped to: Canada, European Union, Great Britain, Japan.

#### **Certifications, Approvals and Ratings**

**NSF** Certified

#### **Technical Documents**

Instructions for Using PIG® Pipe Wrap Repair Kit on Pipes Not Under Pressure

PIG® Multi-Purpose Repair Putty

PIG® Wrap for Pipes



# One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com