









PTY202 4 oz. Tube,6 per box

Top quality resins bond better and stay stronger so repairs last - we guarantee it! Fix it fast and fix it right with PIG Epoxy Putty.

- Customer-favorite PIG Epoxy Putty sticks to almost anything and cures fast
- Made with the highest-quality epoxy resins to bond better and stay stronger; adheres to steel, glass, masonry and most plastics
- Convenient, premeasured epoxy has Parts A and B in one tube ready for kneading
- Cures concrete-hard in 1 hour for drilling, tapping, sanding or painting
- Nontoxic, VOC- and solvent-free putty can be used on potable water lines
- 3- to 5-minute working time
- A great addition to any toolbox or response kit
- PIG Putty is not intended for making structural repairs



# **Specifications**

Style	Repair Putty
Dimensions	7" L
Application	Multi-Purpose
Brand	PIG
Handling Time	3 Minutes
Pipe Pressure	Pressurized, Non-Pressurized
Color	Gray
Pipe Size	Unlimited
Repair Type	Permanent
Temperature Limit	-20°F (-29°C) to 250°F (121°C) Continuous, 300°F (149°C) Intermittent
Volume	4 oz. Tube
Sold as	6 per box
Weight	2.1 lbs.
Composition	<ul><li>15% Epoxy Resins</li><li>1.5% Catalyst</li><li>83.5% Non-Hazardous Proprietary Ingredient</li></ul>

Shelf Life	2 years
UNSPSC	31201607
Pigalog® Page Number	Page 247

# Metric Equivalent

Weight	1 kg
Dimensions	18cm L

#### **Technical Information**

## CountryNoShip

This product is subject to export restrictions and cannot be shipped to: Canada, European Union, Great Britain.

#### **Certifications, Approvals and Ratings**

**NSF** Certified

## **Technical Documents**

## **PIG Putty**

Instructions for PIG Multi-Purpose Epoxy Putty

PIG® Multi-Purpose Repair Putty



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com