

PIG® Multi-Purpose Epoxy Putty

PTY230 .85 oz. Tube, 40 per box

Top quality resins bond better and stay stronger so repairs last - we guarantee it! Fix it fast and fix it right with PIG Epoxy Putty.

- Customer-favorite PIG Epoxy Putty sticks to almost anything and cures fast
- Made with the highest-quality epoxy resins to bond better and stay stronger; adheres to steel, glass, masonry and most plastics
- Convenient, premeasured epoxy has Parts A and B in one tube ready for kneading
- Cures concrete-hard in 1 hour for drilling, tapping, sanding or painting
- Nontoxic, VOC- and solvent-free putty can be used on potable water lines
- 3- to 5-minute working time
- A great addition to any toolbox or response kit
- PIG Putty is not intended for making structural repairs



Specifications

Style	Repair Putty
Dimensions	1.5" L
Application	Multi-Purpose
Brand	PIG
Handling Time	3 Minutes
Pipe Pressure	Pressurized, Non-Pressurized
Color	Gray
Pipe Size	Unlimited
Repair Type	Permanent
Temperature Limit	-20°F (-29°C) to 250°F (121°C) Continuous, 300°F (149°C) Intermittent
Volume	.85 oz. Tube
Sold as	40 per box
Weight	3 lbs.
Composition	15% Epoxy Resins 1.5% Catalyst 83.5% Non-Hazardous Proprietary Ingredient

Shelf Life	2 years
UNSPSC	31201607
Pigalog® Page Number	<u>Page 247</u>

Metric Equivalent

Weight	1.4 kg
Dimensions	3.8cm L

Technical Information

CountryNoShip

This product is subject to export restrictions and cannot be shipped to: Canada, European Union, Great Britain.

Certifications, Approvals and Ratings

NSF Certified

Technical Documents

[PIG Putty](#)

[Instructions for PIG Multi-Purpose Epoxy Putty](#)

[PIG® Multi-Purpose Repair Putty](#)



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com