

PIG® Wet Surfaces Epoxy Putty

PTY259 4 oz. Tube, 6 per box

Special PIG Epoxy Putty is formulated to bond to wet surfaces and cure underwater. Guaranteed to work or your money back.



- Specially formulated with the highest-quality epoxy resins to bond to wet surfaces, even cures underwater!
- Convenient, premeasured epoxy has Parts A and B in one tube so you can fix it fast
- Mixes easily simply by kneading to a uniform color
- Cures concrete-hard in 1 hour; once cured, putty can be drilled, sawed, filed, tapped, machined, sanded or painted
- 25-minute working time
- Resists yellowing from UV
- Ideal for repairing fittings, pipes, electrical connections, leaky gaskets, sinks, tanks and boats
- PIG Putty is not intended for making structural repairs



Specifications

| | |
|-------------------|---|
| Style | Repair Putty |
| Dimensions | 7" L |
| Application | Wet Surface |
| Brand | PIG |
| Handling Time | 25 Minutes |
| Pipe Pressure | Pressurized, Non-Pressurized |
| Color | Gray |
| Pipe Size | Unlimited |
| Repair Type | Permanent |
| Temperature Limit | -40°F (-40°C) to 250°F (121°C) Continuous, 300°F (149°C) Intermittent |
| Volume | 4 oz. Tube |
| Sold as | 6 per box |
| Weight | 3 lbs. |
| Composition | 15% Epoxy Resins 1.5% Catalyst |

| | |
|----------------------|--|
| | 83.5% Non-Hazardous Proprietary Ingredient |
| Shelf Life | 2 years |
| UNSPSC | 31201607 |
| Pigalog® Page Number | <u>Page 247</u> |

Metric Equivalent

| | |
|------------|--------|
| Weight | 1.4 kg |
| Dimensions | 18cm L |

Technical Information

| |
|---------------|
| CountryNoShip |
|---------------|

This product is subject to export restrictions and cannot be shipped to: Canada, European Union, Great Britain.

Technical Documents

PIG Putty

Instructions for PIG Wet Surface Epoxy Putty

PIG® Wet Surface Repair Putty



One Pork Avenue • Tipton, PA 16684-0304
1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com