

PIG® Wet Surfaces Epoxy Putty

PTY259 4 oz. Tube, 6 per box

Special PIG Epoxy Putty is formulated to bond to wet surfaces and cure underwater. Guaranteed to work or your money back.



- Specially formulated with the highest-quality epoxy resins to bond to wet surfaces, even cures underwater!
- Convenient, premeasured epoxy has Parts A and B in one tube so you can fix it fast
- Mixes easily simply by kneading to a uniform color
- Cures concrete-hard in 1 hour; once cured, putty can be drilled, sawed, filed, tapped, machined, sanded or painted
- 25-minute working time
- Resists yellowing from UV
- Ideal for repairing fittings, pipes, electrical connections, leaky gaskets, sinks, tanks and boats
- PIG Putty is not intended for making structural repairs



Specifications

Style	Repair Putty
Dimensions	7" L
Application	Wet Surface
Brand	PIG
Handling Time	25 Minutes
Pipe Pressure	Pressurized, Non-Pressurized
Color	Gray
Pipe Size	Unlimited
Repair Type	Permanent
Temperature Limit	-40°F (-40°C) to 250°F (121°C) Continuous, 300°F (149°C) Intermittent
Volume	4 oz. Tube
Sold as	6 per box
Weight	3 lbs.
Composition	15% Epoxy Resins 1.5% Catalyst

83.5% Non-Hazardous Proprietary Ingredient

Shelf Life 2 years

UNSPSC 31201607

Pigalog® Page Number Page 256

Metric Equivalent

Dimensions 17.8cm L

Weight 1.4 kg

Technical Information

CountryNoShip

This product is subject to export restrictions and cannot be shipped to: Canada, European Union, Great Britain.

Technical Documents

[PIG® Repair Putty](#)

[Instructions for PIG Wet Surface Epoxy Putty](#)

[PIG® Wet Surface Repair Putty](#)



New Pig

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com