

PIG® Steel Epoxy Putty

PTY264 4 oz. Tube, 6 per box

Special PIG Epoxy Putty formulations cover nearly any application. Guaranteed to work or your money back.

- Specially formulated with the highest-quality epoxy resins to bond and blend with ferrous metals
- Convenient, premeasured epoxy has Parts A and B in the same tube
- Mixes easily simply by kneading to a uniform color
- Cures concrete-hard in 1 hour; once cured, putty can be drilled, sawed, filed, tapped, machined, sanded or painted
- Nontoxic, VOC- and solvent-free putty can be used on potable water lines
- 3- to 5-minute working time
- Can be used indoors or out
- A great addition to any toolbox or response kit
- PIG Putty is not intended for making structural repairs



Specifications

Style	Repair Putty
Dimensions	7" L
Application	Steel
Brand	PIG
Handling Time	3 Minutes
Pipe Pressure	Pressurized, Non-Pressurized
Color	Gray
Pipe Size	Unlimited
Repair Type	Permanent
Temperature Limit	-40°F (-40°C) to 250°F (121°C) Continuous, 300°F (149°C) Intermittent
Volume	4 oz. Tube
Sold as	6 per box
Weight	2 lbs.
Composition	15% Epoxy Resins 1.5% Catalyst

	83.5% Non-Hazardous Proprietary Ingredient
Shelf Life	2 years
UNSPSC	31201607
Pigalog® Page Number	Page 247

Metric Equivalent

Weight	.9 kg
Dimensions	18cm L

Technical Information

CountryNoShip

This product is subject to export restrictions and cannot be shipped to Canada.

Certifications, Approvals and Ratings

NSF Certified

Technical Documents

- PIG Putty
- Instructions for PIG Steel Epoxy Putty
- PIG® Steel Repair Putty



One Pork Avenue • Tipton, PA 16684-0304
1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com