

ZIPCRETE™ Self-Leveling Epoxy Resurfacer

PTY312 50 sq. ft. at .0625" Deep Coverage Area, For Concrete, Includes 1 - 5 gal. Pail; 1 - 1 gal. can Resin; 1 - 1 qt. can Hardener; Loose filler sand; 1 - Tint packet

Self-leveling epoxy floor patch provides a smooth, attractive finish.

- Super-strong formulation has a 15,000 psi compressive strength
- Creates a smooth, attractive, easily-cleaned surface
- Resists heavy traffic and corrosion
- Recommended for indoor use, but may be used outdoors if all moisture is removed while epoxy completely sets
- Stable compound is free of harmful chemicals
- For use in areas allowing up to 24 hours of curing



Specifications

Style	Floor Patch Epoxy
Use With	Concrete
Application Temperature	40°F (4°C) to 75°F (24°C)
Brand	MIPCO ZIPCRETE
Coverage Area	50 sq. ft. at .0625" Deep
Cure Time	24 Hours
Color	Gray
Handling Time	20 Minutes
Includes	1 - 5 gal. Pail; 1 - 1 gal. can Resin; 1 - 1 qt. can Hardener; Loose filler sand; 1 - Tint packet
Temperature Limit	50°F (10°C) to 90°F (32°C)
Sold as	1 each
Weight	40 lbs.
# per Pallet	36

Composition

Binder - Modified Epoxy Resin
 Activator - Cycloaliphatic Amine
 Filler - Sand

Includes

1 - 5-Gallon Pail
1 - 1- gal. can Resin
1 - 1- qt. can Hardener
1 - 19 lbs. loose filler Fine sand
1 - Tint Packet

Shelf Life

1 year

UNSPSC

13111001

Pigalog® Page Number

Page 260

Metric Equivalent**Weight**

18.1 kg

Technical Information**StateNoShip**

This product is subject to restrictions and cannot be shipped to Alaska or Hawaii.

USOnly

This product can ONLY be shipped to the United States.

Technical Documents

[Zip-Crete Self-Leveling Epoxy Resurfacer \(Part A\)](#)

[Zip-Crete Self-Leveling Epoxy Resurfacer \(Part B\)](#)

[Zip-Crete Self-Leveling Epoxy Resurfacer \(Part C\)](#)



New Pig

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com