

Sili-Thane™ 803 Sealant

PTY340-1 For Build-A-Berm Barrier, Metals, Masonry, Glass, Plastics & Wood, ext. dia. 2" x 11.25" H, 1 each

Polyether-based adhesive offers superior sealing properties and flexibility.

- Excellent for creating flexible, liquid-tight seals when used with our PIG Build-A-Berm products
- Adheres to aluminum, brass, steel, stainless steel, concrete, brick, stone, glass, ceramic tile, fiberglass, ABS, PVC, polyester, plywood and more
- Provides superior UV resistance, flexibility and a 30-minute, tack-free cure time
- Resistant to mild solvents, hydrocarbons and oils for worry-free use in industrial applications
- Sealant maintains structural integrity in high humidity; won't foam or bubble when applied



Item#	Description	Dimensions	Weight
PTY340-1-BK		ext. dia. 2" x 11.25" H	1.28 lbs.
PTY340-1-WH		ext. dia. 2" x 11.25" H	1.28 lbs.

Metric Equivalent:

Item#	Description	Dimensions	Weight
PTY340-1-BK		ext. dia. 5.1cm x 29cm H	.6 kg
PTY340-1-WH		ext. dia. 5.1cm x 29cm H	.6 kg

Specifications

Style	Adhesive
Use With	Build-A-Berm Barrier, Metals, Masonry, Glass, Plastics & Wood
Dimensions	ext. dia. 2" x 11.25" H
Brand	Polymeric
Repair Type	Permanent
Temperature Limit	-40°F (-40°C) to 195°F (90°C)
Volume	10.3 fl. oz. Cartridge
Sold as	1 each
Weight	1.28 lbs.

Composition	Polyether-Based Adhesive
Shelf Life	1 year
UNSPSC	31201606
Pigalog® Page Number	<u>Page 153</u>

Metric Equivalent

Weight	.6 kg
Dimensions	ext. dia. 5.1cm x 29cm H

Technical Information

CountryShipOnly

This product can ONLY be shipped to: United States, Chile, Colombia, French Polynesia.

Technical Documents

Sili-Thane™ 803 Sealant

Sili-Thane 803 Sealant (White)

Silithane 803 Black Sealant



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com