



## Sili-Thane™ 803 Sealant

PTY340-1 For Build-A-Berm Barrier, Metals, Masonry, Glass, Plastics & Wood, ext. dia. 2" x 11.25" H, 1 each

Polyether-based adhesive offers superior sealing properties and flexibility.

- Excellent for creating flexible, liquid-tight seals when used with our PIG Build-A-Berm products
- Adheres to aluminum, brass, steel, stainless steel, concrete, brick, stone, glass, ceramic tile, fiberglass, ABS, PVC, polyester, plywood and more
- Provides superior UV resistance, flexibility and a 30-minute, tack-free cure time
- Resistant to mild solvents, hydrocarbons and oils for worry-free use in industrial applications
- Sealant maintains structural integrity in high humidity; won't foam or bubble when applied



| Item#       | Description | Dimensions              | Weight    |
|-------------|-------------|-------------------------|-----------|
| PTY340-1-BK |             | ext. dia. 2" x 11.25" H | 1.28 lbs. |
| PTY340-1-WH |             | ext. dia. 2" x 11.25" H | 1.28 lbs. |

### Metric Equivalent:

| Item#       | Description | Dimensions               | Weight |
|-------------|-------------|--------------------------|--------|
| PTY340-1-BK |             | ext. dia. 5.1cm x 29cm H | .6 kg  |
| PTY340-1-WH |             | ext. dia. 5.1cm x 29cm H | .6 kg  |

### Specifications

|                   |                                                               |
|-------------------|---------------------------------------------------------------|
| Style             | Adhesive                                                      |
| Use With          | Build-A-Berm Barrier, Metals, Masonry, Glass, Plastics & Wood |
| Dimensions        | ext. dia. 2" x 11.25" H                                       |
| Brand             | Polymeric                                                     |
| Repair Type       | Permanent                                                     |
| Temperature Limit | -40°F (-40°C) to 195°F (90°C)                                 |
| Volume            | 10.3 fl. oz. Cartridge                                        |
| Sold as           | 1 each                                                        |
| Weight            | 1.28 lbs.                                                     |

|                             |                          |
|-----------------------------|--------------------------|
| <b>Composition</b>          | Polyether-Based Adhesive |
| <b>Shelf Life</b>           | 1 year                   |
| <b>UNSPSC</b>               | 31201606                 |
| <b>Pigalog® Page Number</b> | <u>Page 153</u>          |

## Metric Equivalent

|                   |                          |
|-------------------|--------------------------|
| <b>Weight</b>     | .6 kg                    |
| <b>Dimensions</b> | ext. dia. 5.1cm x 29cm H |

## Technical Information

|                        |
|------------------------|
| <b>CountryShipOnly</b> |
|------------------------|

This product can ONLY be shipped to: United States, Chile, Colombia, French Polynesia.

## Technical Documents

- Sili-Thane™ 803 Sealant
- Sili-Thane 803 Sealant (White)
- Silithane 803 Black Sealant



**One Pork Avenue • Tipton, PA 16684-0304**  
 1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)