


Peel & Seal® Self-Stick Roll Roofing

PTY348 For Patching or Full-Roof Applications, 6" W x 33.5' L, 6 rolls per box

Quick, permanent, weatherproof repairs for gutters, joints and low-slope roofs.

- Peel and press into place without torches, tar, mops or adhesives
- Adheres to nearly any surface without coating or additional materials
- Multiple polymer layers create a durable seal that prevents leaks and resists UV rays
- Top aluminum layer reflects heat to keep buildings cool and reduce energy costs
- Lightweight roll is easy to apply and won't crack, rot and dry like traditional waterproofing materials
- Cuts easily with scissors or utility knife
- Ideal for finishing or spot repairs on industrial buildings, truck trailers, farming facilities and mobile homes



mfm

Item#	Description	Dimensions	Weight
PTY348-SLV		6" W x 33.5' L	30.5 lbs.
PTY348-WH		6" W x 33.5' L	30.5 lbs.

Metric Equivalent:

Item#	Description	Dimensions	Weight
PTY348-SLV		15cm W x 10.2m L	13.8 kg
PTY348-WH		15cm W x 10.2m L	13.8 kg

Specifications

Style	Repair Material; Self-Adhering Roofing System
Use With	Patching or Full-Roof Applications
Dimensions	6" W x 33.5' L
Brand	MFM Building Products Corp
Coverage Area	16.75 sq. ft. per Roll
Repair Type	Permanent

Temperature Limit	-20°F (-29°C) to 170°F (76°C)
Volume	(6) 33.5' L x 6" W Roll
Sold as	6 rolls per box
Weight	30.5 lbs.
# per Pallet	36
Composition	Top - Reflective Aluminum Foil Composite Bottom - Rubberized Asphalt w/ Adhesive Back & Release Paper
Shelf Life	1 year
UNSPSC	72101601

Metric Equivalent

Weight	13.8 kg
Dimensions	15cm W x 10.2m L

Technical Information

US Only

This product can ONLY be shipped to the United States.

Certifications, Approvals and Ratings

ASTM D1970

Technical Documents

[Instructions for Peel & Seal® Self-Stick Roll Roofing](#)



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com