


## Peel & Seal® Self-Stick Roll Roofing

PTY349 For Patching or Full-Roof Applications, 36" W x 33.5' L, 1 roll per box

Quick, permanent, weatherproof repairs for gutters, joints and low-slope roofs.

- Peel and press into place without torches, tar, mops or adhesives
- Adheres to nearly any surface without coating or additional materials
- Multiple polymer layers create a durable seal that prevents leaks and resists UV rays
- Top aluminum layer reflects heat to keep buildings cool and reduce energy costs
- Lightweight roll is easy to apply and won't crack, rot and dry like traditional waterproofing materials
- Cuts easily with scissors or utility knife
- Ideal for finishing or spot repairs on industrial buildings, truck trailers, farming facilities and mobile homes



MFM

Item#	Description	Dimensions	Weight
PTY349-SLV		36" W x 33.5' L	29.75 lbs.
PTY349-WH		36" W x 33.5' L	29.75 lbs.

### Metric Equivalent:

Item#	Description	Dimensions	Weight
PTY349-SLV		91cm W x 10.2m L	13.5 kg
PTY349-WH		91cm W x 10.2m L	13.5 kg

### Specifications

Style	Repair Material; Self-Adhering Roofing System
Use With	Patching or Full-Roof Applications
Dimensions	36" W x 33.5' L
Brand	MFM Building Products Corp
Coverage Area	100.5 sq. ft.
Repair Type	Permanent
Temperature Limit	-20°F (-29°C) to 170°F (76°C)

<b>Volume</b>	33.5' L x 36" W Roll
<b>Sold as</b>	1 roll per box
<b>Weight</b>	29.75 lbs.
<b># per Pallet</b>	36
<b>Composition</b>	Top - Reflective Aluminum Foil Composite Bottom - Rubberized Asphalt w/ Adhesive Back & Release Paper
<b>Shelf Life</b>	1 year
<b>UNSPSC</b>	72101601

## Metric Equivalent

<b>Weight</b>	13.5 kg
<b>Dimensions</b>	91cm W x 10.2m L

## Technical Information

<b>USOnly</b>
---------------

This product can ONLY be shipped to the United States.

## Certifications, Approvals and Ratings

ASTM D1970

## Technical Documents

[Instructions for Peel & Seal® Self-Stick Roll Roofing](#)



**One Pork Avenue • Tipton, PA 16684-0304**  
 1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)