

## Sikaflex® Adhesive

PTY422 For Metals, Masonry, Glass & Wood, 1 each

Confidently bond surfaces under dynamic stress with this one-step Sikaflex adhesive that's specially designed to actively withstand it.

- One-step Sikaflex 252 adhesive bonds with a high-strength hold that actively resists dynamic stresses
- Elastic properties increase when under stress, providing flexibility to protect bond
- Dampens vibrations
- Ideal for manufacturing and transportation industries and other industrial applications
- Can paint it without compromising hold
- Non-corrosive
- This is the recommended adhesive for New Pig's Safeguard Traction Grit line



Item#	Description	Dimensions	Weight
PTY422-BK			.75 lbs.
PTY422-WH			.75 lbs.

### Metric Equivalent:

Item#	Description	Dimensions	Weight
PTY422-BK			.3 kg
PTY422-WH			.3 kg

### Specifications

<b>Style</b>	Adhesive
<b>Use With</b>	Metals, Masonry, Glass & Wood
<b>Sold as</b>	1 each
<b>Weight</b>	.75 lbs.
<b>Composition</b>	1-C polyurethane xylene 1-5% ethylbenzene .1-1% 4,4'-methylenediphenyl diisocyanate .1-1% Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane .1-1% 3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate .1-1%

**Shelf Life** 274 days

**UNSPSC** 31201606

**Pigalog® Page Number** Page 177

## Metric Equivalent

**Weight** .3 kg

## Technical Information

### USOnly

This product can ONLY be shipped to the United States.

## Technical Documents

Sikaflex-252



**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)