

Sikaflex® Adhesive

PTY422 For Metals, Masonry, Glass & Wood, 1 each

Confidently bond surfaces under dynamic stress with this one-step Sikaflex adhesive that's specially designed to actively withstand it.

- One-step Sikaflex 252 adhesive bonds with a high-strength hold that actively resists dynamic stresses
- Elastic properties increase when under stress, providing flexibility to protect bond
- Dampens vibrations
- Ideal for manufacturing and transportation industries and other industrial applications
- Can paint it without compromising hold
- Non-corrosive
- This is the recommended adhesive for New Pig's Safeguard Traction Grit line



Item#	Description	Dimensions	Weight
PTY422-BK			.75 lbs.
PTY422-WH			.75 lbs.

Metric Equivalent:

Item#	Description	Dimensions	Weight
PTY422-BK			.3 kg
PTY422-WH			.3 kg

Specifications

Style	Adhesive
Use With	Metals, Masonry, Glass & Wood
Sold as	1 each
Weight	.75 lbs.
Composition	<p>1-C polyurethane xylene 1-5% ethylbenzene .1-1% 4,4'-methylenediphenyl diisocyanate .1-1% Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane .1-1% 3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate .1-1%</p>

Shelf Life	274 days
UNSPSC	31201606
Pigalog® Page Number	<u>Page 177</u>

Metric Equivalent

Weight	.3 kg
--------	-------

Technical Information

USOnly

This product can ONLY be shipped to the United States.

Technical Documents

Sikaflex-252



One Pork Avenue • Tipton, PA 16684-0304
1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com