

Sikaflex® Sealant

PTY423 For Metals, Masonry, Glass, Plastics & Wood,1 each

Permanently seal more surface types with an elastic hold using this one-step multi-purpose Sikaflex sealant.

- Use this versatile one-step Sikaflex 221 sealant on a wide range of surfaces
- Works well on metals, plastics, ceramics and more
- Gives you a permanent elastic seal
- Resists aging to last over time
- Can sand it and paint it without compromising its hold
- Safely non-corrosive and low-odor
- This is the recommended sealant for New Pig's Safeguard Traction Grit line



Item#	Description	Dimensions	Weight
PTY423-BK			.75 lbs.

PTY423-WH			.75 lbs.
-----------	--	--	----------

Metric Equivalent:

Item#	Description	Dimensions	Weight
PTY423-BK			.3 kg

PTY423-WH			.3 kg
-----------	--	--	-------

Specifications

Style	Adhesive
Use With	Metals, Masonry, Glass, Plastics & Wood
Sold as	1 each
Weight	.75 lbs.
Composition	1-Component Polyurethane Xylene 1-5% 4,4'-Methylenediphenyl Diisocyanate .1-1% Ethylbenzene .1-1% Quartz (SiO2) .1-1%
Shelf Life	1 year
UNSPSC	31201606

Metric Equivalent

Weight	.3 kg
--------	-------

Technical Information

USOnly

This product can ONLY be shipped to the United States.

Technical Documents

Sikaflex-221



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com