

PIG® UV Activated Repair Patch

PTY426 For Metals, Masonry, Glass & Wood,6" W x 9" L,1 each

Quickly repair almost any surface with this UVactivated patch that's easy to apply and holds tough.

- Durable, reinforced polyester/plastic patch starts flexible and hardens once activated
- Easy to apply; just cut, peel and stick to any hard, non-polypropylene surface that's clean and dry
- Fully cures in as few as 5 minutes in direct sunlight or about 15 minutes under UV light (UV flashlight sold separately); begins hardening and holding within first few minutes
- Once fully cured, can drill, tap, sand and paint for a professional look
- Won't shrink or expand during or after curing
- Great for outdoor use; waterproof, weatherresistant and temperature-resistant from -40°F to 392°F
- FDA Approved; non-toxic, and adhesive won't harm skin



Specifications

Pigalog® Page Number

Style	Repair Material
Use With	Metals, Masonry, Glass & Wood
Dimensions	6" W x 9" L
Brand	PIG
Repair Type	Permanent
Sold as	1 each
Color	Gray
Weight	.3 lbs.
Composition	Fiberglass- 20-25% Mineral Fillers- 45-50% Polyester Resin- 18-23% Styrene Monomer- 0.6% by weight
Shelf Life	4 years
UNSPSC	72101601

Page 252

Metric Equivalent

Weight 136 g

Dimensions 15cm W x 23cm L

Technical Information

USOnly

This product can ONLY be shipped to the United States.

Certifications, Approvals and Ratings

FDA Approved

Technical Documents

PIG UV Activated Repair Patch

PIG® UV Activated Repair Patch



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com