

PIG® UV Activated Repair Patch

PTY427 For Metals, Masonry, Glass & Wood,9" W x 12" L,1 each

Quickly repair almost any surface with this UVactivated patch that's easy to apply and holds tough.

- Durable, reinforced polyester/plastic patch starts flexible and hardens once activated
- Easy to apply; just cut, peel and stick to any hard, non-polypropylene surface that's clean and dry
- Fully cures in as few as 5 minutes in direct sunlight or about 15 minutes under UV light (UV flashlight sold separately); begins hardening and holding within first few minutes
- Once fully cured, can drill, tap, sand and paint for a professional look
- Won't shrink or expand during or after curing
- Great for outdoor use; waterproof, weatherresistant and temperature-resistant from -40°F to 392°F
- FDA Approved; non-toxic, and adhesive won't harm skin



Specifications

Style	Repair Material
Use With	Metals, Masonry, Glass & Wood
Dimensions	9" W x 12" L
Brand	PIG
Repair Type	Permanent
Sold as	1 each
Color	Gray
147-1-1-C	
Weight	.55 lbs.
Composition	55 lbs. Fiberglass- 20-25% Mineral Fillers- 45-50% Polyester Resin- 18-23% Styrene Monomer- 0.6% by weight
	Fiberglass- 20-25% Mineral Fillers- 45-50% Polyester Resin- 18-23%
Composition	Fiberglass- 20-25% Mineral Fillers- 45-50% Polyester Resin- 18-23% Styrene Monomer- 0.6% by weight

Metric Equivalent	
Weight	.2 kg
Dimensions	23cm W x 30cm L
Technical Information	
USOnly	
This product can ONLY be shipped to the United States.	
Certifications, Approvals and Ratings	
FDA Approved	

PIG UV Activated Repair Patch

Technical Documents

PIG® UV Activated Repair Patch



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com