

PIG® UV Activated Repair Patch

PTY427 For Metals, Masonry, Glass & Wood, 9" W x 12" L, 1 each

Quickly repair almost any surface with this UV-activated patch that's easy to apply and holds tough.

- Durable, reinforced polyester/plastic patch starts flexible and hardens once activated
- Easy to apply; just cut, peel and stick to any hard, non-polypropylene surface that's clean and dry
- Fully cures in as few as 5 minutes in direct sunlight or about 15 minutes under UV light (UV flashlight sold separately); begins hardening and holding within first few minutes
- Once fully cured, can drill, tap, sand and paint for a professional look
- Won't shrink or expand during or after curing
- Great for outdoor use; waterproof, weather-resistant and temperature-resistant from -40°F to 392°F
- FDA Approved; non-toxic, and adhesive won't harm skin



Specifications

Style	Repair Material
Use With	Metals, Masonry, Glass & Wood
Dimensions	9" W x 12" L
Brand	PIG
Repair Type	Permanent
Sold as	1 each
Color	Gray
Weight	.55 lbs.
Composition	Fiberglass- 20-25% Mineral Fillers- 45-50% Polyester Resin- 18-23% Styrene Monomer- 0.6% by weight
Shelf Life	4 years
UNSPSC	72101601
Pigalog® Page Number	<u>Page 252</u>

Metric Equivalent

Weight .2 kg

Dimensions 23cm W x 30cm L

Technical Information

US Only

This product can ONLY be shipped to the United States.

Certifications, Approvals and Ratings

FDA Approved

Technical Documents

[PIG UV Activated Repair Patch](#)

[PIG® UV Activated Repair Patch](#)



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com