

Aboweld 55-1™ Epoxy Paste for Concrete Repair

PTY600 7.5 cu. in. Coverage Area,For Concrete; Metal; Wood,Includes 1 - 6 oz. Part A Pail; 1 - 6 oz. Part B Pail

Repair concrete in even the most challenging environments, including overhead or underwater, with this tenacious epoxy paste.

- Apply to vertical, overhead and horizontal surfaces without forms; slump resistant up to 3/8 in. thick on vertical surfaces
- Tenacious adhesion and structural strength suitable for even the most punishing environments; even hardens under water
- Shrink-free and chemical resistant
- Ideal for filling cracks, replacing missing concrete and permanently bonding concrete with most rigid materials; use for both industrial and home repairs
- Restores columns, walls, ceilings, foundations, pools, rails, stair risers and treads, sculptures and more



Specifications

Style	Floor Patch Epoxy
Use With	Concrete; Metal; Wood
Application Temperature	60°F (15°C) to 90°F (32°C)
Brand	Abatron
Cure Time	2 to 6 Hours
Coverage Area	7.5 cu. in.
Color	Gray
Handling Time	20 to 30 Minutes
Includes	1 - 6 oz. Part A Pail; 1 - 6 oz. Part B Pail
Temperature Limit	60°F (15°C) to 90°F (32°C)
Sold as	1 each
Weight	1 lb.
Composition	Epoxy Paste
Shelf Life	2 years
UNSPSC	13111001

Metric Equivalent

Weight	.5 kg
--------	-------

Technical Information

US Only

This product can ONLY be shipped to the United States.

Technical Documents

[Aboweld 55-1 Epoxy Paste for Concrete Repair](#)



New Pig

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com