

Aboweld 55-1™ Epoxy Paste for Concrete Repair

PTY601 116 cu. in. Coverage Area,For Concrete; Metal; Wood,Includes 1 - 1 qt. Part A Pail; 1 - 1 qt. Part B Pail



Repair concrete in even the most challenging environments, including overhead or underwater, with this tenacious epoxy paste.

- Apply to vertical, overhead and horizontal surfaces without forms; slump resistant up to 3/8 in. thick on vertical surfaces
- Tenacious adhesion and structural strength suitable for even the most punishing environments; even hardens under water
- Shrink-free and chemical resistant
- Ideal for filling cracks, replacing missing concrete and permanently bonding concrete with most rigid materials; use for both industrial and home repairs
- Restores columns, walls, ceilings, foundations, pools, rails, stair risers and treads, sculptures and more



Specifications

| | |
|-------------------------|--|
| Style | Floor Patch Epoxy |
| Use With | Concrete; Metal; Wood |
| Application Temperature | 60°F (15°C) to 90°F (32°C) |
| Brand | Abatron |
| Cure Time | 2 to 6 Hours |
| Coverage Area | 116 cu. in. |
| Color | Gray |
| Handling Time | 20 to 30 Minutes |
| Includes | 1 - 1 qt. Part A Pail; 1 - 1 qt. Part B Pail |
| Temperature Limit | 60°F (15°C) to 90°F (32°C) |
| Sold as | 1 each |
| Weight | 7 lbs. |
| Composition | Epoxy Paste |
| Shelf Life | 2 years |
| UNSPSC | 13111001 |

Metric Equivalent

| | |
|--------|--------|
| Weight | 3.2 kg |
|--------|--------|

Technical Information

US Only

This product can ONLY be shipped to the United States.

Technical Documents

[Aboweld 55-1 Epoxy Paste for Concrete Repair](#)



New Pig

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com