

## BestBond® Joint Sealant

PTY605 For Concrete; Rigid Surfaces, 2" W x 2.75" L x 11" H, 1 each

Fill and seal joints in concrete with this high-strength, self-leveling liquid epoxy.

- Ideal for permanently filling and sealing control joints, expansion joints and saw cuts
- For use on horizontal substrates
- Higher elongation allows for movement and settling of the concrete
- Hardens quickly and resists water, chemicals and UV
- Shrink-free
- Contains no water or solvents
- For use indoors or outdoors
- 9 fl oz cartridge fits in hand-held caulking gun for easy installation



### Specifications

Style	Repair Material
Use With	Concrete; Rigid Surfaces
Dimensions	2" W x 2.75" L x 11" H
Brand	Abatron
Coverage Area	16 cu. in.
Repair Type	Permanent
Color	Gray
Temperature Limit	50°F (10°C) to 95°F (35°C)
Volume	9 fl. oz. Cartridge
Sold as	1 each
Weight	1 lb.
Composition	Epoxy Liquid
UNSPSC	31201607

### Metric Equivalent

Weight	.5 kg
Dimensions	5.1cm W x 7cm L x 28cm H

### Technical Information

US Only
---------

This product can ONLY be shipped to the United States.

## Technical Documents

BestBond Joint Sealant



**New Pig**

World's best stuff for leaks, drips and spills.

**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)