# Best Annual Random Anchor Barton Anchor Anch

# BestBond® High Strength Epoxy Anchoring Compound

PTY606 For Concrete; Rigid Surfaces,2" W x 2.75" L x 12" H,1 each

Anchor structures using this high-strength, self-leveling liquid epoxy.

- Ideal for permanently anchoring posts, bolts and rebar to concrete, stone, masonry and most rigid surfaces
- For use on horizontal substrates
- High tensile, compressive and pull-out strengths
- Hardens quickly and resists water, chemicals and UV
- Shrink-free
- Contains no water or solvents
- For use indoors or outdoors
- 9 fl oz cartridge fits in hand-held caulking gun for easy installation

## **Specifications**

Style	Repair Material
Use With	Concrete; Rigid Surfaces
Dimensions	2" W x 2.75" L x 12" H
Brand	Abatron
Coverage Area	16 cu. in.
Repair Type	Permanent
Color	Gray
Temperature Limit	50°F (10°C) to 95°F (35°C)
Volume	9 fl. oz. Cartridge
Sold as	1 each
Weight	1 lb.
Composition	Epoxy Liquid
UNSPSC	31201607
Metric Equivalent	
Weight	.5 kg
Dimensions	5.1cm W x 7cm L x 30cm H

# **Technical Information**

### **USOnly**

This product can ONLY be shipped to the United States.

### **Technical Documents**

# BestBond® High Strength Epoxy Anchoring Compound



# One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com