



FerroBond P™ Steel-Filled Epoxy Structural Adhesive Putty

PTY609 1 lb. Kit, 1 each

Permanently repair metal components, whether decorative or structural, as well as most other rigid surfaces by using this steel-filled epoxy that creates a durable adhesive putty.

- Resists wear and tear, even in high impact environments and temperatures up to 212 degrees F (100 degrees C)
- Shrink-free and dimensionally stable; unaffected by atmospheric conditions or water, salt, alkalis, diluted acids, most solvents, oil and grease
- Apply in any thickness
- Cured putty is easy to machine with standard tools and can be painted
- Versatile permanent repair applications are nearly limitless, ranging from decorative or structural metal components to ceramics, glass, fiberglass and most rigid surfaces

ABATRON

Specifications

Style	Repair Putty
Dimensions	3.75" L
Application	Multi-Purpose
Brand	Abatron
Handling Time	1 Hour
Pipe Pressure	Pressurized, Non-Pressurized
Color	Gray
Pipe Size	Unlimited
Repair Type	Permanent
Temperature Limit	212°F (100°C) Maximum Temperature
Volume	1 lb. Kit
Sold as	1 each
Weight	2 lbs.
Composition	Proprietary Epoxy Prepolymer
Shelf Life	2 years
UNSPSC	31201607

Metric Equivalent

Weight	.9 kg
Dimensions	9.5cm L

Technical Information

USOnly

This product can ONLY be shipped to the United States.

Technical Documents

FerroBond P™ Steel-Filled Epoxy Structural Adhesive Putty



New Pig

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com