

# MetalFix P™ Aluminum-Filled Epoxy Structural Adhesive Putty

PTY610 1 lb. Kit, 2 per box

Permanently repair metal components, whether decorative or structural, as well as most other rigid surfaces by using this aluminum-filled epoxy that creates a durable adhesive putty.

- Resists wear and tear, even in high impact environments and temperatures up to 212 degrees F (100 degrees C)
- Shrink-free and dimensionally stable; unaffected by atmospheric conditions or water, salt, alkalis, diluted acids, most solvents, oil and grease
- Apply in any thickness
- Cured putty is easy to machine with standard tools and can be painted
- Versatile permanent repair applications are nearly limitless, ranging from decorative or structural metal components to ceramics, glass, fiberglass and most rigid surfaces



## Specifications

Style	Repair Putty
Dimensions	3.75" L
Application	Multi-Purpose
Brand	Abatron
Handling Time	1 Hour
Pipe Pressure	Pressurized, Non-Pressurized
Color	Gray
Pipe Size	Unlimited
Repair Type	Permanent
Temperature Limit	212°F (100°C) Maximum Temperature
Volume	1 lb. Kit
Sold as	2 per box
Weight	2 lbs.
Composition	Proprietary Epoxy Prepolymer
Shelf Life	2 years
UNSPSC	31201607

## Metric Equivalent

**Weight** .9 kg

**Dimensions** 9.5cm L

## Technical Information

### US Only

This product can ONLY be shipped to the United States.

## Technical Documents

MetalFix P™ Aluminum-Filled Epoxy Structural Adhesive Putty



**New Pig**

World's best stuff for leaks, drips and spills.

**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)