

## **PIG® Skimmer Oil-Only Absorbent Sock**

SKM203 ext. dia. 3" x 10' L, Each absorbs up to 2.5 gal., 6 socks per box

Skims oil from chemical baths in open-top dip tanks.

- UV- and chemical-resistant polypropylene skin and filler absorb oils but repel water-based liquids
- Tough enough for acid baths and phosphates tanks
- Ideal for skimming oil off acid or caustic baths or for use in other acidic environments
- Meets ANSI and MIL-SPEC standards for static decay
- Attached string allows socks to be tied down, tied together or dipped into tanks
- PIG Skimmer Socks float at the surface for easy retrieval
- Absorbs and retains oil-based liquids - including lubricants and fuels - without taking in a drop of water
- Nobody knows more about socks than New Pig
- we invented them!



### Specifications

|                  |  |
|------------------|--|
| Absorbency Range | 10 - 19.9 gal.                                 |
| Dimensions       | ext. dia. 3" x 10' L                           |
| Recycled Content | 98% Pre-Consumer Recycled Polypropylene Filler |
| Absorbency       | Up to 15 gal. per box                          |
| Absorbency per   | Up to 2.5 gal. per sock                        |
| Application      | Skimming                                       |
| Color            | White  |
| Brand            | PIG  |
| Filler           | Polypropylene                                  |
| Fluid Absorbed   | Oils; Fuels; Oil-Based Liquids (Not Water)     |
| Skin/Outer Mesh  | Skin - Polypropylene                           |
| Sold as          | 6 socks per box                                |
| Weight           | 15 lbs.  |

# per Pallet

24

## Metric Equivalent

|                |                        |
|----------------|------------------------|
| Absorbency per | Up to 9.5 L per sock   |
| Absorbency     | Up to 56.8 L per box   |
| Weight         | 6.8 kg                 |
| Dimensions     | ext. dia. 7.6cm x 3m L |

## Technical Information

### Certifications, Approvals and Ratings

ANSI/ESD STM11.11,MIL-STD-3010C

### Technical Documents

[UV-Resistance Comparison Testing of Spunbond and Meltblown](#)

[Technical Data Sheet for PIG® Oil Only Absorbents](#)

[40 CFR 112.7](#)

[40 CFR 122.26](#)



**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)