



## PIG® Pipe Leak Diverter

TLS248 Diverter; Hanging Straps, Install With Hanging Straps, 18" x 18"

Catches pipe leaks or condensation to protect equipment, inventory and people.

- Hangs from a leaking pipe to catch nuisance leaks and channel them to a floor drain, collection container or portable storage tank
- Fast and economical way to prevent damage until pipe repairs can be made
- Nonpermeable tarp is vinyl-coated for strength and durability; resists punctures, UV and mildew for long life
- Built-in brass grommets and included 14"-long rubber straps make it easy to hang from an overhead pipe
- Choose yellow for high visibility, gray to blend with plant ceilings or clear to monitor leaks
- Flow rate of 3.33 gallons per minute when used with a 1/2" ID hose
- Hose and collection container sold separately

Item#	Description	Dimensions	Weight
TLS248-CL	Clear	ext. dia. 18" x 18" H	2 lbs.
TLS248-GY	Gray	ext. dia. 18" x 18" H	2 lbs.
TLS248-YW	Yellow	ext. dia. 18" x 18" H	2 lbs.

### Metric Equivalent:

Item#	Description	Dimensions	Weight
TLS248-CL	Clear	ext. dia. 45.7cm x 45.7cm H	.9 kg
TLS248-GY	Gray	ext. dia. 45.7cm x 45.7cm H	.9 kg
TLS248-YW	Yellow	ext. dia. 45.7cm x 45.7cm H	.9 kg

### Specifications

<b>Dimensions</b>	ext. dia. 18" x 18" H
<b>Brand</b>	PIG
<b>Contains</b>	Diverter; Hanging Straps
<b>Drainage Hose Included</b>	No
<b>Hanging Straps Included</b>	Yes
<b>Hose Connector</b>	.75"
<b>Installation Method</b>	Hanging Straps
<b>Shape</b>	Circle
<b>Sold as</b>	1 each

<b>Weight</b>	2 lbs.
<b># per Pallet</b>	192
<b>Composition</b>	Diverter (Colors) - PVC, Polyester Diverter (Clear) - PVC w/ Polyester Reinforcement Straps - Rubber
<b>Application</b>	Pipes
<b>Flow Rate</b>	3.33 gal./Minute
<b>Includes</b>	1 - Leak Diverter 1 - Hose Connector Replacement Set (TLS645) 4 - Rubber Hanging Straps (TLS470)
<b>UNSPSC</b>	24141506
<b>Pigalog® Page Number</b>	<a href="#">Page 261</a>

## Metric Equivalent

<b>Dimensions</b>	ext. dia. 45.7cm x 45.7cm H
<b>Weight</b>	.9 kg

## Technical Information

### Technical Documents

[Instructions for PIG Leak Diverter Systems](#)

### Disclaimers

#### Maximum Working Temperature

Not suitable for temperatures over 170°F/77°C.



**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)