

VAC-U-MAX® Industrial Wet Vacuum

TLS271 Air Powered, VAC-U-MAX

Wet vac quickly cleans up liquids.



- Must be used with 55-gallon open-head steel drum without clamps for cleaning spills in one step
- VAC-U-MAX Vacuum includes static-conductive PVC 1 1/2" x 15' hose, aluminum wand, floor tool and crevice tool
- Produces a maximum static lift of 215" H2O and 110 SCFM suction
- Input operating range from 37-70 SCFM at 60 psig
- Ideal for cleaning up spills of water or machine oils, removing oil from sumps and other containment, and picking up metal chips and other small debris; use with PIG SpillBlocker Dikes for best results
- Requires a minimum .5" air line for operation
- Not suitable for flammable or corrosive liquids (see TLS417, VAC-U-MAX® Flammable Fuels and Oils Vacuum)

Specifications

Capacity	55 gal.
Color	Blue
Air Flow	100 CFM
Brand	VAC-U-MAX
Maximum Suction Power	215" Sealed Pressure
Powered By	Air
Spill Kit Accessory Type	Vacuums
Use With Flammables	No
Sold as	1 each
Weight	52.6 lbs.
# per Pallet	6
Composition	Hose - PVC Hand Tool - Aluminum Floor Tool - Plastic Wand - Aluminum
Power Requirements	Air: 35 SCFM at 60 PSI (Minimum)
UNSPSC	47121602
Pigalog® Page Number	Page 280

Metric Equivalent

Technical Information

Disclaimers

Flammables Warning

Not suitable for flammable or corrosive liquids.

One-Year Parts Warranty

New Pig is confident that our product will perform well and according to your expectations. In the event that a powered equipment product does not perform to those expectations due to mechanical or electrical malfunction or as a result of defects in workmanship or design, it is covered by New Pig's One-Year Parts Warranty. New Pig will replace free-of-charge any parts needed to restore the product to its original condition. New Pig will even pay for the cost of shipping the parts!

**New Pig**

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com