

VAC-U-MAX® Fuels and Flammable Oils Vacuum

TLS417 Air Powered

Designed especially to help you safely lift fuels, flammable oils and chemically compatible semi-solids.



- Designed with advanced safety features that help prevent ignition of fuels and flammable oils, including a static dissipative hose, anti-sparking inlet with flame arrestor, grounding lug and non-sparking vacuum tools
- Ideal for use with diesel, gasoline, kerosene, JP fuels, oils and semi-solids that are chemically compatible with the vacuum
- Completely air-driven to minimize risk of explosion
- Single-jet venturi with variable orifice produces maximum flow rate with minimum compressed air requirements
- Recovers one gallon of liquid per second and operates on a minimum of 35 scfm at 60 psi
- Automatic shutoff prevents accidental drum overfilling
- Included 55-gallon collection drum meets NFPA requirements as a storage container
- Operates below 80 Db to help meet OSHA Noise Exposure requirements in 29 CFR 1910.95
- Requires a minimum .5" air line for operation

Specifications

Air Flow	100 CFM
Brand	VAC-U-MAX
Capacity	55 gal.
Maximum Suction Power	208" Sealed Pressure
Powered By	Air
Power Requirements	Air: 35 SCFM at 60 PSI (Minimum)
Color	Red/Yellow
Spill Kit Accessory Type	Vacuums
Use With Flammables	Yes
Sold as	1 each
Weight	54 lbs.
# per Pallet	1
Composition	Vacuum - Carbon Steel

Drum - Steel
Hose - Buna-N
Crevice Tool, Squeegee - Aluminum
Lid Gasket - Buna-N

Includes

1 - 55-gallon Vacuum
1 - 1.5" x 25' Hose
1 - 1.5" Two Bend Floor Wand
1 - 14" Squeegee
1 - 1.5" Crevice Tool
1 - Caster Assembly
1 - .5" x 25' Static-conductive Hose
1 - .5" Quick Disconnect Coupling

UNSPSC

47121602

Metric Equivalent

Weight

24.5 kg

Technical Information



New Pig

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com