

PIG® High Flow Roof Leak Diverter Tarp

TLS675 6' x 6', Leak Diverter Tarp; Hose, Install With Hanging Straps



High flow design catches and diverts up to 10 gallons per minute to prevent high volume ceiling leaks from becoming a big problem.

- Easy and quick way to prevent damage to your facility caused by roof or ceiling leaks
- 3" diameter flat hose drains up to 10 gallons of liquid per minute
- Heavy-duty vinyl-coated tarp resists punctures, UV and mildew and lasts multiple deployments
- Pinched corners create a funnel to channel liquids to a drain or collection container without overflowing or sagging; engineered with leak-proof seams and connections
- Brass grommets resist tearing and make installation easy; multiple hanging points add stability and preserve funnel shape
- Cut drain hose for a custom fit; insert 90-degree elbow between hose sections to prevent kinking (hose and elbow fitting included)
- Ideal for washdowns or after heavy rains
- Collection container and hanging straps sold separately



Item#	Description	Dimensions	Weight
TLS675-TR		6' W x 6' L	7.7 lbs.

Metric Equivalent:

Item#	Description	Dimensions	Weight
TLS675-TR		183cm W x 183cm L	3.5 kg

Specifications

Dimensions	6' W x 6' L
Application	Roofs
Brand	PIG
Contains	Leak Diverter Tarp; Hose
Drainage Hose	Included
Flow Rate	10 gal./Minute

Hanging Straps	Sold Separately
Hose Connector	3"
Installation Method	Hanging Straps
Shape	Square
Sold as	1 each
Weight	7.7 lbs.
# per Pallet	240

Composition	Diverter: Reinforced Vinyl Hose: Vinyl Elbow: PVC
Includes	1 - 6' W x 6' L Leak Diverter Tarp 1 - 3" W x 25' L Flat Hose 1 - 90° Elbow

UNSPSC	24141506
Pigalog® Page Number	Page 251

Metric Equivalent

Weight	3.5 kg
Dimensions	183cm W x 183cm L

Technical Information

Technical Documents

[PIG High Flow Roof Leak Diverter](#)



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com