

Workbench Style Double Wall Waste Oil Tank

TLS930 Storage Capacity 180 gal., 28" W x 60" L x 41" H, 1 each

Evacuate, transfer and store used oil with this workbench-style tank and pump-assist system.

- UL Listed double-wall tank provides 110-percent secondary containment
- Meets UL 142 specifications and Uniform Fire Code and NFPA 30 requirements
- UL Listed, 1 in. air-operated diaphragm pump has a 30 gpm capacity
- Automatic pump shutoff to prevent overfilling
- 3/4 in. x 10 ft suction hose with quick-connect coupler
- 2 in. drop tube with camlock fitting and dust cover



Specifications

Style	Double Wall
Dimensions	28" W x 60" L x 41" H
Storage Capacity	180 gal.
Brand	John Dow
Meets UL 142 Standard	Meets UL 142 Standard
Opening Dimensions	2" Dia.
Color	Brown
Use With Flammables	Yes
Sold as	1 each
Weight	738 lbs.
Composition	Steel
UNSPSC	20142901

Metric Equivalent

Storage Capacity	681.3 L
Weight	334.8 kg
Dimensions	71cm W x 152cm L x 104cm H

Technical Information

Certifications, Approvals and Ratings

NFPA Code 30,UL 142,UL Listed

Technical Documents

40 CFR 112.7

40 CFR 122.26



New Pig

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com