













# Workbench Style Double Wall Waste Oil **Tank**

TLS931 Storage Capacity 245 gal.,28" W x 74" L x 40" H,1 each

Evacuate, transfer and store used oil with this workbench-style tank and pump-assist system.

- UL Listed double-wall tank provides 110percent secondary containment
- Meets UL 142 specifications and Uniform Fire Code and NFPA 30 requirements
- UL Listed, 1 in. air-operated diaphragm pump has a 30 gpm capacity
- Automatic pump shutoff to prevent overfilling
- 3/4 in. x 10 ft suction hose with quick-connect coupler
- 2 in. drop tube with camlock fitting and dust cover



# **Specifications**

Style	Double Wall
Dimensions	28" W x 74" L x 40" H
Storage Capacity	245 gal.
Brand	John Dow
Meets UL 142 Standard	Meets UL 142 Standard
Opening Dimensions	2" Dia.
Color	Brown
Use With Flammables	Yes
Sold as	1 each
Weight	927 lbs.
Composition	Steel
UNSPSC	20142901
Metric Equivalent	

927.3 L

420.5 kg

71cm W x 188cm L x 102cm H

### **Technical Information**

**Storage Capacity** 

Weight

**Dimensions** 

#### **USOnly**

This product can ONLY be shipped to the United States.

# **Certifications, Approvals and Ratings**

NFPA Code 30,UL 142,UL Listed

#### **Technical Documents**

40 CFR 112.7

40 CFR 122.26



# One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com