

Workbench Style Double Wall Waste Oil Tank

TLS932 Storage Capacity 285 gal., 33" W x 67" L x 62" H, 1 each

Evacuate, transfer and store used oil with this workbench-style tank and pump-assist system.

- UL Listed double-wall tank provides 110-percent secondary containment
- Meets UL 142 specifications and Uniform Fire Code and NFPA 30 requirements
- UL Listed, 1 in. air-operated diaphragm pump has a 30 gpm capacity
- Automatic pump shutoff to prevent overfilling
- 3/4 in. x 10 ft suction hose with quick-connect coupler
- 2 in. drop tube with camlock fitting and dust cover



Specifications

Style	Double Wall
Dimensions	33" W x 67" L x 62" H
Storage Capacity	285 gal.
Brand	John Dow
Meets UL 142 Standard	Meets UL 142 Standard
Opening Dimensions	2" Dia.
Color	Brown
Use With Flammables	Yes
Sold as	1 each
Weight	883 lbs.
Composition	Steel
UNSPSC	20142901

Metric Equivalent

Storage Capacity	1078.7 L
Weight	400.5 kg
Dimensions	84cm W x 170cm L x 157cm H

Technical Information

USOnly

This product can ONLY be shipped to the United States.

Certifications, Approvals and Ratings

NFPA Code 30,UL 142,UL Listed

Technical Documents

40 CFR 112.7

40 CFR 122.26



New Pig

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com