

## Workbench Style Double Wall Waste Oil Tank

TLS933 Storage Capacity 500 gal., 40" W x 88.5" L x 44" H, 1 each

Evacuate, transfer and store used oil with this workbench-style tank and pump-assist system.

- UL Listed double-wall tank provides 110-percent secondary containment
- Meets UL 142 specifications and Uniform Fire Code and NFPA 30 requirements
- UL Listed, 1 in. air-operated diaphragm pump has a 30 gpm capacity
- Automatic pump shutoff to prevent overfilling
- 3/4 in. x 10 ft suction hose with quick-connect coupler
- 2 in. drop tube with camlock fitting and dust cover



### Specifications

Style	Double Wall
Dimensions	40" W x 88.5" L x 44" H
Storage Capacity	500 gal.
Brand	John Dow
Meets UL 142 Standard	Meets UL 142 Standard
Opening Dimensions	2" Dia.
Color	Brown
Use With Flammables	Yes
Sold as	1 each
Weight	1300 lbs.
Composition	Steel
UNSPSC	20142901

### Metric Equivalent

Storage Capacity	1892.5 L
Weight	589.7 kg
Dimensions	102cm W x 225cm L x 112cm H

### Technical Information

CountryShipOnly
-----------------

This product can ONLY be shipped to the United States or Canada.

## Certifications, Approvals and Ratings

NFPA Code 30,UL 142,UL Listed

## Technical Documents

40 CFR 112.7

40 CFR 122.26



**New Pig**

World's best stuff for leaks, drips and spills.

**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)