



PIG® Water-Activated Flood Bag

WTR009 Ideal For Stacking, Retaining Walls, 12" W x 24" L x 3.5" H When Fully Saturated, 10 each

Super absorbent flat bags swell up on contact with water to become a solid, heavy barrier to quickly dam and divert floodwater.

- Stack 26"-long sandbag replacements to create a retaining wall in flood-prone areas when water is coming
- Lightweight, compact and easy to handle before activated, unlike standard sandbags which are heavy, messy and labor-intensive
- Stack and stagger up to three rows high; build even higher retaining walls by using a pyramid layout
- NOTE: Not for use with salt water



Specifications

| | |
|---------------------------------|--|
| Traffic | Non-Weight Bearing |
| Dimensions When Fully Saturated | 12" W x 24" L x 3.5" H When Fully Saturated |
| Height When Fully Saturated | 3.5" When Fully Saturated |
| Weight When Fully Saturated | 32 lbs. each When Fully Saturated |
| Capacity | 4 gal. per Bag |
| Color | Black |
| Dimensions | 15" W x 26" L x 0.25" H |
| Brand | PIG |
| Ideal For | Stacking, Retaining Walls |
| Install/Deploy Type | Temporary/Removable Barrier |
| Temperature Limit | Works from 32°F to 180°F |
| Sold as | 10 per bag |
| Weight | 4.7 lbs. |
| # per Pallet | 100 |
| Composition | Skin - Polypropylene Filler - Super Absorbent Polymer (SAP) |
| UNSPSC | 24101907 |
| Pigalog® Page Number | Page 163 |

Metric Equivalent

| | |
|------------|-----------------------------|
| Dimensions | 38.1cm W x 66cm L x 6.4mm H |
|------------|-----------------------------|

Weight

2.1 kg

Technical Information

Technical Documents

[Instructions for PIG Water-Activated Flood Bags & Barriers](#)

[PIG® Water Activated Flood Barriers](#)

Disclaimers

[Saltwater Notice](#)

Not for use with saltwater flooding.



New Pig

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com