









WTR204 ext. dia. 1.5" x 11" L,Each absorbs up to 7.2 oz.,3 per box

Drop a Water Hog into a fuel-tank port for fast absorption of water without absorbing any fuel.

- Removes water from fuel tanks; absorbs water but not fuel
- Prevents frozen fuel lines and gelled fuel
- Combats rust, algae and filter blockage to help prevent premature engine wear and potential failure
- Heavy-duty rip-stop cotton skin with unbreakable plastic casing ensures snag-free use in closed tanks and ports
- Attached string allows easy deployment and retrieval



Specifications

| Absorbency Range | 0 - 0.9 gal. |
|-----------------------|---|
| Dimensions | ext. dia. 1.5" x 11" L |
| Absorbency | Up to 21.6 oz. per box |
| Absorbency per | Up to 7.2 oz. |
| Application | Remove Water From Fuel |
| Brand | PIG |
| Clip/Ring | Retrieval Cord - Nylon, Eyelet - Metal |
| Filler | Sodium Acrylate Copolymer |
| Fluid Absorbed | Water-Based Liquids Only |
| Retrieval Line Length | 4' |
| Skin/Outer Mesh | Skin - Cotton, Outer Mesh - Polypropylene |
| Sold as | 3 per box |
| Weight | .6 lbs. |
| UNSPSC | 47131904 |
| Pigalog® Page Number | Page 63 |

Metric Equivalent

| Absorbency per | Up to 212.9 mL |
|----------------|--------------------------|
| Absorbency | Up to 638.7 mL per box |
| Weight | .3 kg |
| | <u> </u> |
| Dimensions | ext. dia. 3.8cm x 28cm L |

Technical Information

Technical Documents

Instructions for PIG Water Hog



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com