


Flex Seal Liquid® Flood Protection

WTR252 For Metals, Masonry, Glass, Plastics & Wood, 6.5" W x 6.5" L x 7.5" H, 1 each

Seeps into gaps, cracks and openings and dries to a strong, flexible, rubberized and watertight coating. It seals out water, while remaining flexible.

- Can be brushed, rolled or poured directly onto the surface or on top of other Flood Protection products
- Use as a final coat of protection to help seal any small pinholes or openings that may have been missed
- Penetrates deep into gaps, cracks and openings
- Once floodwaters recede, Flood Protection Liquid can be easily removed
- Flood liquid will dry to the touch in approximately 3 to 6 hours and fully cure in approximately 24-48 hours
- Allow product to fully cure before floodwaters arrive
- Flood Liquid begins to cure when exposed to the air - always keep lid on tight during and after use
- The coverage for one coat of the 122oz Flood Liquid, when applied 2" inches wide, is approximately 244 linear feet



Specifications

Style	Flood Protection
Use With	Metals, Masonry, Glass, Plastics & Wood
Dimensions	6.5" W x 6.5" L x 7.5" H
Brand	Flex Seal Family of Products
Coverage Area	244 linear ft. at 2" Wide
Temperature Limit	32°F (0°C) to 120°F (49°C)
Color	Hi-Viz Yellow
Volume	122 fl. oz. Container
Sold as	1 each
Weight	10.5 lbs.
Composition	Rubberized Liquid

Metric Equivalent

Weight 4.8 kg

Dimensions 17cm W x 17cm L x 19cm H

Technical Information

Certifications, Approvals and Ratings

UL Listed

Technical Documents

Flex Seal Liquid Flood Protection



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com