

## Flex Paste® Flood Protection Cartridge

WTR253 For Metals, Masonry, Glass, Plastics & Wood, 1 each



Starts out as a thick paste to fill openings then dries to a strong, rubberized coating. It seals out water, air and moisture, while remaining flexible.

- Starts out as a thick paste that can be pushed deep into all types of openings and hard-to-reach areas
- Dries to a strong, flexible rubberized barrier that seals out water, air and moisture
- Once floodwaters recede, Flood Paste can be easily removed
- Use as a base coat for your first layer of protection
- Use on windows, doors, garage doors and all types of seams, casings, thresholds, conduits, vents and ducts, keyholes and more
- Flood Paste will dry to the touch in approximately 2-6 hours and fully cure in approximately 24-48 hours
- Allow product to fully cure before floodwaters arrive
- Flood Paste begins to cure when exposed to the air
- Flood Protection Cartridge (9oz): A 1/4" inch bead will cover approximately 21 linear feet
- Flood Protection Cartridge (28oz): A 1/4" inch bead will cover approximately 62 linear feet



Item#	Description	Dimensions	Weight
WTR253-28OZ	28 oz.		

WTR253-9OZ	9 oz.		
------------	-------	--	--

### Metric Equivalent:

Item#	Description	Dimensions	Weight
WTR253-28OZ	28 oz.		

WTR253-9OZ	9 oz.		
------------	-------	--	--

### Specifications

<b>Style</b>	Flood Protection
--------------	------------------

<b>Use With</b>	Metals, Masonry, Glass, Plastics & Wood
-----------------	---

<b>Brand</b>	Flex Seal Family of Products
<b>Temperature Limit</b>	32°F (0°C) to 120°F (49°C)
<b>Sold as</b>	1 each
<b>Composition</b>	Waterproof Paste
<b>Color</b>	Hi-Viz Yellow
<b>UNSPSC</b>	31201606
<b>Pigalog® Page Number</b>	<u>Page N21</u>

## Metric Equivalent

## Technical Information

### US Only

This product can ONLY be shipped to the United States.

### Certifications, Approvals and Ratings

UL Listed

### Technical Documents

[Flex Paste Flood Protection \(YLW\)](#)



**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)