

## Flex Paste® Flood Protection Cartridge

WTR253 For Metals, Masonry, Glass, Plastics & Wood, 1 each

Starts out as a thick paste to fill openings then dries to a strong, rubberized coating. It seals out water, air and moisture, while remaining flexible.

- Starts out as a thick paste that can be pushed deep into all types of openings and hard-to-reach areas
- Dries to a strong, flexible rubberized barrier that seals out water, air and moisture
- Once floodwaters recede, Flood Paste can be easily removed
- Use as a base coat for your first layer of protection
- Use on windows, doors, garage doors and all types of seams, casings, thresholds, conduits, vents and ducts, keyholes and more
- Flood Paste will dry to the touch in approximately 2-6 hours and fully cure in approximately 24-48 hours
- Allow product to fully cure before floodwaters arrive
- Flood Paste begins to cure when exposed to the air
- Flood Protection Cartridge (9oz): A 1/4" inch bead will cover approximately 21 linear feet
- Flood Protection Cartridge (28oz): A 1/4" inch bead will cover approximately 62 linear feet



| Item#       | Description | Dimensions | Weight |
|-------------|-------------|------------|--------|
| WTR253-28OZ | 28 oz.      |            |        |

|            |       |  |  |
|------------|-------|--|--|
| WTR253-9OZ | 9 oz. |  |  |
|------------|-------|--|--|

### Metric Equivalent:

| Item#       | Description | Dimensions | Weight |
|-------------|-------------|------------|--------|
| WTR253-28OZ | 28 oz.      |            |        |

|            |       |  |  |
|------------|-------|--|--|
| WTR253-9OZ | 9 oz. |  |  |
|------------|-------|--|--|

### Specifications

|       |                  |
|-------|------------------|
| Style | Flood Protection |
|-------|------------------|

|          |   |
|----------|---|
| Use With | Metals, Masonry, Glass, Plastics & Wood |
|----------|---|

|                      |                              |
|----------------------|------------------------------|
| Brand                | Flex Seal Family of Products |
| Temperature Limit    | 32°F (0°C) to 120°F (49°C)   |
| Sold as              | 1 each                       |
| Composition          | Waterproof Paste             |
| Color                | Hi-Viz Yellow                |
| UNSPSC               | 31201606                     |
| Pigalog® Page Number | <u>Page N21</u>              |

Metric Equivalent

Technical Information

USOnly

This product can ONLY be shipped to the United States.

Certifications, Approvals and Ratings

UL Listed

Technical Documents

Flex Paste Flood Protection (YLW)



**One Pork Avenue • Tipton, PA 16684-0304**  
1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)