

## Flex Seal Liquid® Flood Protection

WTR261 For Metals, Masonry, Glass, Plastics & Wood, 3.8" W x 3.375" L x 4" H, 1 each

Seeps into gaps, cracks and openings and dries to a strong, flexible, rubberized and watertight coating. It seals out water, while remaining flexible.

- Can be brushed, rolled or poured directly onto the surface or on top of other Flood Protection products
- Use as a final coat of protection to help seal any small pinholes or openings that may have been missed
- Penetrates deep into gaps, cracks and openings
- Once floodwaters recede, Flood Protection Liquid can be easily removed
- Flood liquid will dry to the touch in approximately 3 to 6 hours and fully cure in approximately 24-48 hours
- Allow product to fully cure before floodwaters arrive
- Flood Liquid begins to cure when exposed to the air - always keep lid on tight during and after use
- The coverage for one coat of the 10oz Flood Liquid, when applied 2" wide, is approximately 20 linear feet



## Specifications

Style	Flood Protection
Use With	Metals, Masonry, Glass, Plastics & Wood
Dimensions	3.8" W x 3.375" L x 4" H
Brand	Flex Seal Family of Products
Coverage Area	20 linear ft. at 2" Wide
Temperature Limit	32°F (0°C) to 120°F (49°C)
Color	Hi-Viz Yellow
Volume	10 fl. oz. Container
Sold as	1 each
Weight	1 lb.
Composition	Rubberized Liquid

UNSPSC	31211504
Pigalog® Page Number	Page N22

## Metric Equivalent

Weight	.5 kg
Dimensions	9.7cm W x 8.6cm L x 10cm H

## Technical Information

### Certifications, Approvals and Ratings

UL Listed

### Technical Documents

Flex Seal Liquid Flood Protection



**One Pork Avenue • Tipton, PA 16684-0304**  
1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)