



Flex Seal Liquid® Flood Protection

WTR262 For Metals, Masonry, Glass, Plastics & Wood, 4.5" W x 4.5" L x 5" H, 1 each

Seeps into gaps, cracks and openings and dries to a strong, flexible, rubberized and watertight coating. It seals out water, while remaining flexible.

- Can be brushed, rolled or poured directly onto the surface or on top of other Flood Protection products
- Use as a final coat of protection to help seal any small pinholes or openings that may have been missed
- Penetrates deep into gaps, cracks and openings
- Once floodwaters recede, Flood Protection Liquid can be easily removed
- Flood liquid will dry to the touch in approximately 3 to 6 hours and fully cure in approximately 24-48 hours
- Allow product to fully cure before floodwaters arrive
- Flood Liquid begins to cure when exposed to the air - always keep lid on tight during and after use
- The coverage for one coat of the 28oz container of Flood Liquid, when applied 2" inches wide, is approximately 56 linear feet



Specifications

Style	Flood Protection
Use With	Metals, Masonry, Glass, Plastics & Wood
Dimensions	4.5" W x 4.5" L x 5" H
Brand	Flex Seal Family of Products
Coverage Area	56 linear ft. at 2" Wide
Temperature Limit	32°F (0°C) to 120°F (49°C)
Color	Hi-Viz Yellow
Volume	28 fl. oz. Container
Sold as	1 each
Weight	2.5 lbs.
Composition	Rubberized Liquid

Metric Equivalent

Weight 1.1 kg

Dimensions 11cm W x 11cm L x 13cm H

Technical Information

Certifications, Approvals and Ratings

UL Listed

Technical Documents

Flex Seal Liquid Flood Protection



New Pig

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com